

MX-RD-Pro

LCD Digital Tube Rotator

Features

- LCD display of speed and time
- Circular rotating action, gives gentle but effective mixing
- Adjustable speed range from 10 to 70 rpm
- Adjustable angle from 0 to 90°
- Brushless motor ideal for extended use, and longer life
- Wide variety of accessories are available

Applications

Laboratory Tube Rotators are ideal for Biochemistry, Molecular Biology and Clinical applications. Provides a gentle but effective mixing of biological samples in 1.5ml to 50ml micro tubes, used in a variety of applications including immune precipitations, prevention of blood coagulation, latex diagnostics etc.



Specifications	MX-RD-Pro
Motor type	Brushless DC motor
Tilt angle	0-90°
Speed range	10-70rpm
Speed display	LCD
Timer display	LCD
Timer	1-1199min
Operation mode	Continuous / timer
Voltage,Frequency	100-240V, 50/60Hz
Power	40W
Dimension [D × W × H]	280 × 210 × 300mm
Permissible ambient temperature and humidity	5-40°C,80%RH
Protection class	IP21

Disk Accessories Type-1 Cat. No.18900160

Used for MX-RD-Pro
for 1.5mLx60 centrifuge tubes holder

**Disk Accessories Type-2** Cat. No.18900161

Used for MX-RD-Pro
for 15mLx16 centrifuge tubes holder

**Disk Accessories Type-3** Cat. No.18900162

Used for MX-RD-Pro
for 50mLx8 centrifuge tubes holder

**Disk support rods**

Cat. No.18900140

4pcs in a group
use with disk accessories

**Rotisserie Accessory Type-3**

Cat. No.18900144

Used for MX-RL-Pro, for 50mLx24
centrifuge tubes held horizontally

**Rotisserie Accessory Type-4**

Cat. No.18900145

Used for MX-RL-Pro, for 1.5mLx32
centrifuge tubes held vertically

**Rotisserie Accessory Type-1**

Cat. No.18900142

Used for MX-RL-Pro, for 1.5mLx48
centrifuge tubes held horizontally

**Rotisserie Accessory Type-5**

Cat. No.18900146

Used for MX-RL-Pro, for 15mLx16
centrifuge tubes held vertically

**Rotisserie Accessory Type-2**

Cat. No.18900143

Used for MX-RL-Pro, for 15mLx24
centrifuge tubes held horizontally

**Rotisserie Accessory Type-6**

Cat. No.18900147

Used for MX-RL-Pro, for 50mLx16
centrifuge tubes held vertically

